





Wilo Pumps and Pumping Systems

Wilo-Atmos GIGA N, Wilo-MISO, Wilo-FD, Wilo-Non Clog Pumps End Suction Pumps



	Application: → Water Distribution → Water Treatment Plant → Agriculture → Process Sea Water → Sewage → Drainage → Cooling Tower → ETP / CETP → Heating → Air Conditioning → Imbibition/Raw Juice in Sugar → Paper -Pulp handling -Consistency up to 5 % → All Juice, Molasses, Lime Water, Black Liquor → De watering
Wilo Atmos GIGA-N/MISO/FD Volume Flow Q Max :	2200 m3/hr
Wilo Atmos GIGA-N/MISO/FD Delivery Head Max :	170 mtr
Special features Wilo-Atmos GIGA N :	 → Energy-saving thanks to increased overall efficiency through improved hydraulics and the use of IE3 motors → Cataphoretic coating of all cast components for high corrosion resistance and long service life → Universally usable thanks to standardised dimensions, a range of motor options and impellers made of different materials
Wilo Non – Clog Pumps Volume Flow Q Max :	8000 m3/hr
Wilo Non – Clog Pumps Delivery Head Max :	60 mtr
Special features Wilo-Non Clog :	 → Mounting: Horizontal/Vertical → Casing with Two hand hole inspection cover → Heavy Duty Antifriction Bearings → Mechanical seal /Gland packing → Large free passage upto 200 mm → Grease lubrication anti-frication bearing → Delivery flange orientation change possible. → Pump can be offered with Cerum coating

www.sapphirefluidsystems.in sapphire@fluidsystems.co.in