



Pioneering for You

wilo

Wilo-Medana CH1-L

Non-self-priming Multistage horizontal centrifugal pumps





Field of application	Cooling circuits, Car wash
Duty chart	
Construction	Non-self-priming Multistage horizontal centrifugal pumps
Application	Pumping of process water and drinkingwater for: irrigation, pressure boosting, industrial applications
Volume flow Q_{max}	24 m ³ /h
Delivery head H_{max}	69 m
Special features	<ul style="list-style-type: none"> → Captive nuts on connections (option) → Cathaphoretic-coated lantern → Oblong hole for fixation → Compact design → ACS approval
Technical data	<ul style="list-style-type: none"> → Mains connection: 1~230 V, 50/60 Hz – 3~380/400/460 V, 50/60 Hz → Rated pressure: 10 bar → Fluid temperature: -20 °C to 120 °C → Ambient temperature: -15 °C to 50 °C → Protection class: IP55
Equipment/function	<ul style="list-style-type: none"> → Pump housing and impellers made of stainless steel → AC motor: 3~ > 0.75 AC IE3, 3~ < 0.75 AC IE2 → AC motor: 1~ AC IE1/IE2 → Threaded connection

Address:

SAPPHIRE FLUID SYSTEMS
No.143/144, Ground Floor, Kempegowda Layout,
Outer Ring Road, Laggere, Bangalore – 560 058
T +91 99000 87727

Website:

www.sapphirefluidsystems.in
sapphire@fluidsystems.co.in

<https://www.facebook.com/people/Sapphire-Fluid-Systems/61566589806616/>